




**MINIATURE FUSES**  
GLASS TUBE **M**

Size **5 x 25 mm**      Rated voltage **250 V**      medium time lag      Standard **not standardized**

Rated current	Part No.	Rated breaking capacity	Weight (kg/100)	Pack
32 mA	172 525	50 A	0.12	100
50 mA	172 525	50 A	0.12	100
63 mA	172 525	50 A	0.12	100
80 mA	172 525	50 A	0.12	100
100 mA	172 525	50 A	0.12	100
125 mA	172 525	50 A	0.12	100
160 mA	172 525	50 A	0.12	100
200 mA	172 525	50 A	0.12	100
250 mA	172 525	50 A	0.12	100
315 mA	172 525	50 A	0.12	100
400 mA	172 525	50 A	0.12	100
500 mA	172 525	50 A	0.12	100
630 mA	172 525	50 A	0.12	100
800 mA	172 525	50 A	0.12	100
1 A	172 525	50 A	0.12	100
1.25 A	172 525	50 A	0.12	100
1.6 A	172 525	80 A	0.12	100
2 A	172 525	80 A	0.12	100
2.5 A	172 525	80 A	0.12	100
3.15 A	172 525	80 A	0.12	100
4 A	172 525	80 A	0.12	100
5 A	172 525	80 A	0.12	100
6.3 A	172 525	80 A	0.12	100
8 A	172 525	80 A	0.12	100
10 A	172 525	80 A	0.12	100



**Pre-arcing time limits**

Part No. 172 525

Rated current	1.5 I <sub>n</sub>	2.75 I <sub>n</sub>	4 I <sub>n</sub>	10 I <sub>n</sub>
32 mA	> 1 h	100 ms	20 ms	5 ms
10 A		20 s	2 s	100 ms

