


**MINIATURE FUSES**  
**CERAMIC TUBE**
**T**

Size **6.3 x 32 mm** Rated voltage **500 V** time lag Standard **not standardized**

Rated current	Part No.	Voltage drop mV	Pre-arcing I <sup>2</sup> t <sub>s</sub> -value A <sup>2</sup> s	Rated breaking capacity	Power dissipation W	cURus UR	Weight (kg/100)	Pack
100 mA	189 140	3600	0.05	1500 A *	1.3		0.24	100
125 mA	189 140	3400	0.08	1500 A *	1.4		0.24	100
160 mA	189 140	3000	0.12	1500 A *	1.5		0.24	100
200 mA	189 140	2500	0.20	1500 A *	1.6		0.24	100
250 mA	189 140	2000	0.35	1500 A *	1.7		0.24	100
315 mA	189 140	1800	0.50	1500 A *	1.8		0.24	100
400 mA	189 140	1600	0.80	1500 A *	2.0		0.24	100
500 mA	189 140	450	0.32	1500 A *	0.6	✓	0.24	100
630 mA	189 140	400	0.60	1500 A *	0.7	✓	0.24	100
800 mA	189 140	350	1.0	1500 A *	0.8	✓	0.24	100
1 A	189 140	350	1.5	1500 A *	0.9	✓	0.24	100
1.25 A	189 140	300	3.1	1500 A *	1.0	✓	0.24	100
1.6 A	189 140	200	5.2	1500 A *	1.1	✓	0.24	100
2 A	189 140	180	10	1500 A *	1.2	✓	0.24	100
2.5 A	189 140	160	19	1500 A *	1.3	✓	0.24	100
3.15 A	189 140	150	37	1500 A *	1.4	✓	0.24	100
4 A	189 140	140	68	1500 A *	1.5	✓	0.24	100
5 A	189 140	135	80	1500 A *	2.2	✓	0.24	100
6.3 A	189 140	110	215	1500 A *	2.2	✓	0.24	100
8 A <sup>1</sup>	189 140	110	370	1500 A *	2.6	✓	0.24	100
10 A <sup>1</sup>	189 140	100	620	1500 A *	3.0	✓	0.24	100
12.5 A <sup>1</sup>	189 140	100	1300	1500 A *	3.5	✓	0.24	100
16 A <sup>1</sup>	189 140	100	2500	1500 A *	4.0	✓	0.24	100

Size **6.3 x 32 mm** Rated voltage **440 V** time lag Standard **not standardized**

Rated current	Part No.	Voltage drop mV	Pre-arcing I <sup>2</sup> t <sub>s</sub> -value A <sup>2</sup> s	Rated breaking capacity	Power dissipation W	cURus UR	Weight (kg/100)	Pack
20 A <sup>1</sup>	189 140	100	3400	1500 A	6		0.24	100
25 A <sup>1</sup>	189 140	100	5600	1500 A	8		0.24	100

Size **6.3 x 32 mm** Rated voltage **250 V** time lag Standard **not standardized**

Rated current	Part No.	Voltage drop mV	Pre-arcing I <sup>2</sup> t <sub>s</sub> -value A <sup>2</sup> s	Rated breaking capacity	Power dissipation W	cURus UR	Weight (kg/100)	Pack
32 A <sup>1</sup>	189 140	80	3900	1500 A	10		0.24	100

<sup>1</sup> Consideration should be given to heat dissipation.

\* @ 500 V and 10 kA @ 440 V DC