




**MINIATURE FUSES WITH INDICATOR
CERAMIC TUBE** **F**

Size **5 x 25 mm** Rated voltage **450 V** **fast acting** **Lloyds registered**

Rated current	Part No.	Voltage drop mV	Color code	Rated breaking capacity	Weight (kg/100)	Pack
500 mA	70 089 13	700	white	70 kA	0.13	100
1 A	70 089 13	300	red	70 kA	0.13	100
1.25 A	70 089 13	250	violet	70 kA	0.13	100
1.6 A	70 089 13	400	orange	70 kA	0.13	100
2 A	70 089 13	400	blue	70 kA	0.13	100
2.5 A	70 089 13	350	yellow	70 kA	0.13	100
3.15 A	70 089 13	300	black	70 kA	0.13	100
4 A	70 089 13	200	brown	70 kA	0.13	100
6.3 A	70 089 13	150	green	70 kA	0.13	100
10 A	70 089 13	130	red	70 kA	0.13	100

Note: Suitable fuse holder panel mounting Part No. 71 044 03 and screw cap Part No. 72 044 02 see cataloge MAR



Pre-arcing time limits

Rated current	1.5 I _n	1.9 I _n	2.1 I _n	5 I _n	7 I _n
500 mA	> 1 h	-	< 1 h	< 0.05 s	-
4 A		-	-	-	-
6.3 A	> 1 h	< 1 h	-	-	< 0.1 s
10 A		-	-	-	-

