

# HV Expulsion cut-out fuselinks



## Specifications

**Voltage Rating:** 7.2-34.5kV  
**Speeds** K - fast  
 T - slow

**O/L Capacity** 150% for both speeds  
**Amp Range:** 1-200A  
**Approvals:** complies with ANSI/NEMA  
**Ratings:** 1, 2, 3, 6, 8, 10, 12, 15, 20, 25, 30, 40, 50, 65, 70, 80, 100, 140, 200A

**CHANCE**

## Description

Fusetek expulsion links are universal semi-enclosed buttonhead pattern fuse-links for use in standard expulsion distribution cut-outs.

They are available in 'K' (fast) or 'T' (slow) speed and have industry standard, removeable button heads. Their braided leads are tin-plated copper and of sufficient length for all standard voltage ratings encountered in the field.

Part Numbers		
Amps	K Speed	T Speed
1	M1KA23	M1TA23
2	M2KA23	M2TA23
3	M3KA23	M3TA23
6	M6KA23	M6TA23
8	M8KA23	M8TA23
10	M10KA23	M10TA23
12	M12KA23	M12TA23
15	M15KA23	M15TA23
20	M20KA23	M20TA23
25	M25KA23	M25TA23
30	M30KA23	M30TA23
40	M40KA23	M40TA23
50	M50KA23	M50TA23
65	M65KA23	M65TA23
80	M80KA23	M80TA23
100	M100KA23	M100TA23
140	M140KA23	M140TA23
200	M200KA23	M200TA23

